



820TE

BATTERY TYPE	LFP
RATED STORAGE ENERGY	70.5 kWh
OPERATING WEIGHT	6,600 kg
RATED LOAD CAPACITY	2,000 kg
STANDARD BUCKET SIZE	1.2 m ³
STANDARD BREAKOUT FORCE	61 kN
STANDARD DUMP CLEARANCE	2,620 mm



B A T T E R Y E L E C T R I C V E H I C L E

TOUGH WORLD. TOUGH EQUIPMENT.

820TE SPECIFICATIONS >>>

POWER BATTERY

Battery Type	LFP
Rated Storage Energy	70.5 kWh
Nominal Voltage	309 V
System Voltage	DC24 V
BMS Protection Level	IP67
Cooling Type	Intelligent temperature control liquid cooling
Recommended Charger	≤ 80 kW
Charging Time (80kW Charging Power)	≤ 60 min

DRIVE MOTOR

Peak Power	50 kW
Protection Level	IP67
Ambient Temperature	- 40 ~ 85°C
Cooling Type	Intelligent temperature control liquid cooling
Altitude	≤ 5,000 m

HYDRAULIC MOTOR

Peak Power	60 kW
Protection Level	IP67
Ambient Temperature	- 40 ~ 85°C
Cooling Type	Intelligent temperature control liquid cooling
Altitude	≤ 5,000 m

TRANSMISSION

Manufacturer	LiuGong
Number of Speeds, fwd / rev	2 / 1
Maximum Travel Speed, fwd	40 km/h
Maximum Travel Speed, rev	19 km/h
Transmission Type	Fixed-axis power shift

AXLES

Type	LiuGong wet axle
Axle Oscillation	± 8°
Tire Size	405/70R20

WORKING HYDRAULICS

System	Variable single pump
Operation	Single electric-control joystick
Work Pump	Variable displacement piston pump (single-pump system)
Work Pressure	23.5 MPa

STEERING HYDRAULICS

System	Large displacement steering gear
Steering Pump	Variable displacement piston pump (single-pump system)
Steering Relief Pressure	19 MPa

BRAKES

Service Brake Type	Full hydraulic braking
Service Brake Actuation	Hydraulic wet brake
Parking Brake Type	Disc
Parking Brake Actuation	Hydraulic brake cylinder

LOADER ARM PERFORMANCE


Operating Weight	6,600 kg
Bucket Capacity	1.2 m ³
Tipping Load - Straight	4,350 kg
Tipping Load - Full Turn	3,650 kg
Raise Time	4.7 s
Dump Time	1.1 s
Float Down Time	4.0 s
Fastest Total Cycle Time	9.8 s
Bucket Breakout Force	61 kN
A Maximum Hinge Pin Height	3,408 mm
B Dump Clearance at Full Height Discharge	2,620 mm
C Dump Reach at Full Height Discharge	850 mm
D Maximum Digging Depth, Bucket Level	95 mm
S ₁ Bucket Rollback at Ground Level	45°
S ₂ Bucket Rollback at Carry	49.5°
S ₃ Bucket Rollback at Maximum Height	60°
S ₄ Maximum Dump Angle at Full Height	45°

DIMENSIONS

E Ground Clearance	350 mm
G Wheelbase	2,150 mm
H Cab Height	2,520 mm
J Wheel Tread	1,520 mm
K Width over Tires	1,925 mm
L Length with Bucket Down	5,894 mm
M Turn Angle, Either Side	38°
P Rear Angle of Departure	30°
R ₁ Turning Radius, Bucket Carry	4,749 mm
R ₂ Turning Radius, Outside of Tire	3,953 mm
W Width over Bucket	2,225 mm

SERVICE CAPACITIES

Anti-freeze	25 L
Hydraulic Reservoir	54 L
Axle, Front / Rear	13 / 13 L
Transmission	4 L



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China

T: +86 772 3886124

E: overseas@liugong.com

www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. Liugong standard and optional equipment may vary from region to region. Please consult your Liugong dealer for information specific to your area.

02/2025 Designed by Liugong
Replace the previous versions of 02/2025